


CATM3

Terminal Type - CATM3, Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 32 A, Rated cross-section - 4.0 mm², connection method: Bolt Connection - Screwdriver Operated, number of connections: 2, cross-section: 2.5 mm² - 4 mm², mounting type: TS32

Product Accessories

Cover Profile		
PCCM20NV	Width : 20.00 mm Thickness : 1.00 mm Length : 45.50 mm	
PCCM30NV	Width : 30.00 mm Thickness : 1.00 mm Length : 45.50 mm	
PCC3NV	Width : 300.00 mm Thickness : 1.50 mm Length : 48.50 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPS4NV	Height : 28.50 mm Width : 2.50 mm Length : 46.00 mm	
Insertion Bridge		
ASL1-2W	Width : 16.00 mm Pitch : 10.00 mm Length : 22.50 mm	
ASL1-10W	Width : 96.00 mm Pitch : 10.00 mm Length : 22.50 mm	
ASL1-3W	Width : 26.00 mm Pitch : 10.00 mm Length : 22.50 mm	
ASL1-4W	Width : 36.00 mm Pitch : 10.00 mm Length : 22.50 mm	
ASL1-5W	Width : 46.00 mm Pitch : 10.00 mm Length : 22.50 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	