










CBT100

Terminal Type - CBT100, Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 125 A, Rated cross-section -35 mm², connection method: Bolt Connection - Nut Driver operated, number of connections: 2, cross-section: 6 mm² - 35 mm², mounting type: TS32



Product Accessories

Cover Profile		
PCCM52K	Width : 52.00 mm Thickness : 1.25 mm Length : 49.40 mm	
PCCM78K	Width : 78.00 mm Thickness : 1.40 mm Length : 49.70 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

Datasheet

End Cover		
EPS5/6	Height : 30.50 mm Width : 3.00 mm Length : 52.00 mm	

Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	