




## **CBT110T**

Terminal Type - CBT110T , High Current connectors, nominal voltage: 1000 V, nominal current: 150 A, Rated cross-section - 50 mm<sup>2</sup>, connection method: Bolt connection -Nuts are slotted for screwdriver operation, number of connections: 2, cross-section: 35 mm<sup>2</sup> - 50 mm<sup>2</sup>, mounting type: TS32

### Product Accessories

<b>Cover Profile</b>		
PCP110	Width : 32.00 mm Thickness : 1.50 mm Length : 129.50 mm	
<b>DIN Rail Perforated</b>		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>End Clamp</b>		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN10	Width : 10.00 mm	

Partition Plate		
BPA110	Height : 66.00 mm Width : 3.00 mm Length : 125.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	