

CST16

Terminal Type - CST16, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 76 A , Rated cross-section - 16 mm², connection method: Screw connection, number of connections: 2, cross-section: 6 mm² - 25 mm², mounting type: TS32

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPY	Height : 41.90 mm Width : 2.50 mm Length : 44.90 mm	
Fixed Bridge		
CCLA16-2W	Height : 20.00 mm Pitch : 12.00 mm Length : 21.00 mm	
CCLA16-10W	Height : 20.00 mm Pitch : 12.00 mm Length : 117.00 mm	
CCLA16-3W	Height : 20.00 mm Pitch : 12.00 mm Length : 33.00 mm	
CCLA16-4W	Height : 20.00 mm Pitch : 12.00 mm Length : 45.00 mm	
CCLA16-5W	Height : 20.00 mm Pitch : 12.00 mm Length : 57.00 mm	
CCLA16-6W	Height : 20.00 mm Pitch : 12.00 mm Length : 69.00 mm	
Marker For Terminal Blocks		
LABEL KN10	Width : 10.00 mm	
Partition Plate		
BPY	Height : 66.00 mm Width : 3.00 mm Length : 65.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Switching Jumper		
LSR10-16	Width : 6.00 mm	
RSL16	Thickness : 1.60 mm Pitch : 12.00 mm Length : 21.00 mm	
Warning Label		
WL16	Width : 30.00 mm Thickness : 1.50 mm Length : 50.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	