







CST6WS

Terminal Type - CST6WS , Feed Through Terminal block, nominal voltage: 800 V, nominal current: 41 A , Rated cross-section - 6.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS32 , colour :KHAKHI

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	
Fixed Bridge		
CCLA6-2W	Height : 20.00 mm Pitch : 8.00 mm Length : 13.50 mm	
CCLA6-10W	Height : 20.00 mm Pitch : 8.00 mm Length : 78.10 mm	
CCLA6-3W	Height : 20.00 mm Pitch : 8.00 mm Length : 21.60 mm	
CCLA6-4W	Height : 20.00 mm Pitch : 8.00 mm Length : 29.70 mm	
CCLA6-5W	Height : 20.00 mm Pitch : 8.00 mm Length : 37.70 mm	
CCLA6-6W	Height : 20.00 mm Pitch : 8.00 mm Length : 45.80 mm	
Insertion Bridge		
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm	

Insertion Bridge		
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL6	Thickness : 1.20 mm Pitch : 8.00 mm Length : 13.80 mm	
Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

