



## CST70

Terminal Type - CST70, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 192 A , Rated cross-section - 75 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross-section: 10 mm<sup>2</sup> - 95 mm<sup>2</sup>, mounting type: TS32

### Product Accessories

DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EP70	Height : 78.50 mm Width : 4.00 mm Length : 76.50 mm	
Marker For Terminal Blocks		
LABEL KN17	Width : 17.00 mm	

<b>Marker carriers</b>		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	