


CUT10

Terminal Type - CUT10 , Feed-through terminal block, nominal voltage: 750 V, nominal current: 57 A, Rated cross-section - 10.0 mm², connection method: Screw connection, number of connections: 2, cross section: 1.5 mm² - 16 mm², mounting type: TS32

Product Accessories

| Cover Profile | | |
|-----------------------|---|---|
| PCK3 | Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm |  |
| Cover Profile Carrier | | |
| UHDD | Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm |  |
| DIN Rail Perforated | | |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
| End Clamp | | |
| SCS | Height : 26.90 mm Length : 21.00 mm |  |
| SCSN | Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm |  |
| SCUP | Height : 34.00 mm Length : 44.75 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |

| End Cover | | |
|-------------------------|--|---|
| EPX | Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm |  |
| Fixed Bridge | | |
| CCLA10-2W | Height : 20.00 mm Pitch : 10.00 mm Length : 17.30 mm |  |
| CCLA10-10W | Height : 20.00 mm Pitch : 10.00 mm Length : 97.50 mm |  |
| CCLA10-3W | Height : 20.00 mm Pitch : 10.00 mm Length : 27.30 mm |  |
| CCLA10-4W | Height : 20.00 mm Pitch : 10.00 mm Length : 37.30 mm |  |
| CCLA10-5W | Height : 20.00 mm Pitch : 10.00 mm |  |
| CCLA10-6W | Height : 20.00 mm Pitch : 10.00 mm Length : 57.40 mm |  |
| CCLA10-7W | Height : 20.00 mm Pitch : 10.00 mm Length : 67.40 mm |  |
| CCLA10-8W | Height : 20.00 mm Pitch : 10.00 mm Length : 77.40 mm |  |
| Insertion Bridge | | |
| SLC10N-2W | Width : 17.50 mm Pitch : 10.00 mm Length : 26.50 mm |  |
| SLC10N-10W | Width : 97.50 mm Pitch : 10.00 mm Length : 26.50 mm |  |

| Insertion Bridge | | |
|-------------------------|---|---|
| SLC10N-4W | Width : 37.50 mm Pitch : 10.00 mm Length : 26.50 mm |  |
| SLC10N-6W | Width : 57.50 mm Pitch : 10.00 mm Length : 26.50 mm |  |
| Partition Plate | | |
| KBXF | Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm |  |
| Switching Jumper | | |
| LSR10-16 | Width : 6.00 mm |  |
| RSL10 | Thickness : 1.60 mm Pitch : 10.00 mm Length : 17.00 mm |  |
| Warning Label | | |
| WL10 | Width : 28.00 mm Thickness : 1.50 mm Length : 39.00 mm |  |
| Marker carriers | | |
| GMC | Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm |  |
| SCUDDMLH | Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm |  |