



DPBB185N

Terminal Type - DPBB185N, High Current connectors, nominal voltage: 1000 V, Rated cross-section - 185 mm², nominal current: 353 A, connection method: Bolt connection, number of connections: 2, cross-section: 70 mm² - 185 mm², mounting type: TS 35/15, TS 32

Product Accessories

Cover Profile		
PCP240-2W	Width : 111.00 mm Thickness : 1.50 mm Length : 186.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Marker For Terminal Blocks		
LABEL KN10	Width : 10.00 mm	
Partition Plate		
BPA 185/240	Height : 82.40 mm Width : 3.00 mm Length : 180.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	