

DPBB70

Terminal Type - DPBB70, High current connectors, nominal voltage: 1000 V, nominal current: 192 A, Rated cross-section – 70 mm², connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² - 70 mm², AWG: 6 - 2/0, mounting type: TS 35/7.5, TS 35/15, TS 32

Product Accessories

| Cover Profile | | |
|------------------------|---|---|
| PCP120 | Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm |  |
| DIN Rail Perforated | | |
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| End Clamp | | |
| SCUP | Height : 34.00 mm Length : 44.75 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |

| End Clamp | | |
|-----------------------------------|--|---|
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| Fixed Bridge | | |
| CCLADPBB70-2W | Width : 19.30 mm Thickness : 3.00 mm Pitch : 37.20 mm Length : 52.20 mm |  |
| CCLADPBB70-3W | Width : 19.30 mm Thickness : 3.00 mm Pitch : 37.20 mm Length : 89.40 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN10 | Width : 10.00 mm |  |
| Partition Plate | | |
| BPN70 | Height : 67.50 mm Width : 3.00 mm Length : 125.00 mm |  |
| Marker carriers | | |
| SCUDDMLH | Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm |  |