

DPSC5.08WF-5W

Terminal Type - DPSC5.08WF - 5W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 10, cross section: 0.2 mm² - 2.5 mm², Rated cross section - 2.5 mm² , mounting type: TS35/7.5 , TS35/15

Product Accessories

| DIN Rail Perforated | | |
|-----------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN5.08 | Pitch : 5.08 mm |  |
| Tool | | |
| DPSCCOT | Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm |  |