

## KUFH4

Terminal Type - KUFH4, Fuse terminal block, nominal voltage: 800 V, nominal current: 12 A, Rated cross-section – 4 mm<sup>2</sup>, suitable size of cartridge fuse: 6.35X32 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 24 -10, mounting type: TS 35/7.5, TS 35/15, TS 32

### Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

<b>End Clamp</b>		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
EPFH	Height : 41.90 mm Width : 1.50 mm Length : 71.25 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN 9	Width : 9.00 mm	
<b>Partition Plate</b>		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	

**Marker carriers**

SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	
---------	---	---

