

## **KUT25**


Terminal Type - KUT25 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 101 A, connection method: Screw connection, number of connections: 2, Rated cross section: 25 mm<sup>2</sup>, cross section: 6 mm<sup>2</sup> - 25 mm<sup>2</sup>, AWG: 2-10, mounting type: TS 35/7.5 , TS 35/15 , and TS 32

### Product Accessories

<b>Cover Profile</b>		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
<b>Cover Profile Carrier</b>		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPT	Height : 46.90 mm Width : 1.50 mm Length : 45.00 mm	
Fixed Bridge		
CCLA25-2W	Height : 24.00 mm Pitch : 12.00 mm Length : 21.00 mm	
CCLA25-10W	Height : 24.00 mm Pitch : 12.00 mm Length : 117.00 mm	
CCLA25-3W	Height : 24.00 mm Pitch : 12.00 mm Length : 33.00 mm	

<b>Fixed Bridge</b>		
CCLA25-4W	Height : 24.00 mm Pitch : 12.00 mm Length : 45.00 mm	
CCLA25-5W	Height : 24.00 mm Pitch : 12.00 mm Length : 57.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN12	Width : 12.00 mm	
<b>Partition Plate</b>		
KBT	Height : 53.00 mm Width : 1.50 mm Length : 59.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
<b>Switching Jumper</b>		
LSR10-16	Width : 6.00 mm	
RSL25	Thickness : 1.60 mm Pitch : 12.00 mm Length : 21.00 mm	
<b>Warning Label</b>		
WL16	Width : 30.00 mm Thickness : 1.50 mm Length : 50.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

Marker carriers		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	