











## **KUT6N**



Terminal Type - KUT6N , Feed-through terminal block for photo voltaic applications , nominal voltage: 1000 V, nominal current: 41 A, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 20 - 8 , mounting type: TS 35/7.5, TS 35/15 , TS 32

### Product Accessories

<b>Cover Profile</b>		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
<b>Cover Profile Carrier</b>		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
KPXN	Height : 41.50 mm Width : 1.50 mm Length : 41.50 mm	
<b>Fixed Bridge</b>		
CCLA6N-2W	Height : 17.60 mm Pitch : 8.05 mm Length : 13.50 mm	
CCLA6N-10W	Height : 17.60 mm Pitch : 8.05 mm Length : 77.25 mm	
CCLA6N-3W	Height : 17.60 mm Pitch : 8.05 mm Length : 21.65 mm	

<b>Fixed Bridge</b>		
CCLA6N-4W	Height : 17.60 mm Pitch : 8.05 mm Length : 29.70 mm	
CCLA6N-5W	Height : 17.60 mm Pitch : 8.05 mm Length : 37.75 mm	
<b>Insertion Bridge</b>		
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN8	Width : 8.00 mm	
<b>Partition Plate</b>		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	

Switching Jumper		
LSR6N	Height : 22.20 mm Width : 5.00 mm	
RSL6N		

Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	