

KUTD10NV

Terminal Type - KUTD10NV , Disconnecting terminal block, nominal voltage: 800 V, nominal current: 61 A, Rated cross-section- 10 mm², connection method: Screw connection, number of connections: 2, cross section: 1.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Product Accessories

Cover Profile		
BPSCACP		
Cover Profile Carrier		
BPSCA	Height : 89.30 mm Width : 10.00 mm Length : 90.00 mm	
KBFA	Height : 74.40 mm Width : 4.80 mm Length : 90.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCNL	Height : 44.10 mm Width : 9.50 mm Length : 50.00 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPTDNV	Height : 48.50 mm Thickness : 1.50 mm Length : 61.00 mm	
Insertion Bridge		
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm	

Insertion Bridge		
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm	

Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	