



MBT4

Terminal Type - MBT 4 , Mini and Micro Feed-through terminal block, nominal voltage: 630 V, nominal current: 30 A, Rated cross-section: 2.5 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.2 mm² - 4 mm², mounting type: TS 15

Product Accessories

| DIN Rail Perforated | | |
|---------------------|---|---|
| CHM | Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm |  |
| End Clamp | | |
| SCMN | Height : 18.00 mm Width : 6.10 mm Length : 23.50 mm |  |
| End Cover | | |
| MP1 | Height : 26.30 mm Width : 1.00 mm Length : 28.00 mm |  |
| Fixed Bridge | | |
| SLU4-2W | Height : 13.00 mm Pitch : 6.00 mm Length : 10.40 mm |  |
| SLU4-10W | Height : 13.00 mm Pitch : 6.00 mm Length : 58.40 mm |  |
| SLU4-3W | Height : 13.00 mm Pitch : 6.00 mm Length : 16.40 mm |  |
| SLU4-4W | Height : 13.00 mm Pitch : 6.00 mm Length : 22.40 mm |  |
| SLU4-5W | Height : 13.00 mm Pitch : 6.00 mm Length : 28.40 mm |  |

| Marker For Terminal Blocks | | |
|----------------------------|---|---|
| LABEL U6 | Pitch : 6.00 mm |  |
| Partition Plate | | |
| MBX | Height : 36.70 mm Width : 1.50 mm Length : 42.70 mm |  |

