

## OAT2.5



Terminal Type - OAT2.5 , Feed through terminal block with secured hinged cover, nominal voltage: 1000 V, nominal current: 41 A, Rated cross-section - 6.0 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 1.5 mm<sup>2</sup> - 6.0 mm<sup>2</sup>, AWG: 20 - 14, mounting type: TS 35/7.5, TS 35/15 , TS 32

### Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
OEP 2.5	Height : 33.50 mm Width : 1.50 mm Length : 43.50 mm	
<b>Insertion Bridge</b>		
OSL2.5-2W	Width : 15.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-10W	Width : 87.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-4W	Width : 33.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-5W	Width : 48.00 mm Pitch : 9.00 mm Length : 25.50 mm	

Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	