




## SPT35

Terminal Type - SPT35 , High current connectors with secured hinged cover, nominal voltage: 1000 V, Rated cross-section - 35 mm<sup>2</sup>, nominal current: 140 A, connection method: Bolt connection, number of connections: 2, cross-section: 10 mm<sup>2</sup> - 35 mm<sup>2</sup> , AWG: 8 - 2 , mounting type: TS 35/7.5, TS 35/15

### Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Fixed Bridge		
CCLASPT35-2W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 27.00 mm Length : 42.00 mm	
CCLASPT35-3W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 27.00 mm Length : 69.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	