

## SUT1.5

Terminal Type - SUT1.5, Mini and Micro Feed-through terminal block, nominal voltage: 320 V, nominal current: 18 A, Rated cross-section - 1.5 mm<sup>2</sup>, connection method: Screw clamp connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: TS 15

### Product Accessories

DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
End Clamp		
SCMN	Height : 18.00 mm Width : 6.10 mm Length : 23.50 mm	
End Cover		
ES2	Height : 21.40 mm Width : 1.50 mm Length : 23.50 mm	
Fixed Bridge		
CCLA1.5-2W	Height : 11.00 mm Pitch : 5.00 mm Length : 9.00 mm	
CCLA1.5-10W	Height : 11.00 mm Pitch : 5.00 mm Length : 48.40 mm	
CCLA1.5-3W	Height : 11.00 mm Pitch : 5.00 mm Length : 13.00 mm	
CCLA1.5-4W	Height : 11.00 mm Pitch : 5.00 mm Length : 18.00 mm	
CCLA1.5-5W	Height : 11.00 mm Pitch : 5.00 mm Length : 24.20 mm	

Marker For Terminal Blocks		
LABEL KN5	Width : 5.00 mm	
Partition Plate		
MBX	Height : 36.70 mm Width : 1.50 mm Length : 42.70 mm	

