


## UBDD4




Terminal Type - UBDD 4 , Multi level terminal block, nominal voltage: 630 V, nominal current: 32 A, connection method: Screw connection, number of connections: 4, Rated Cross section: 4 mm<sup>2</sup>, cross section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 24 - 10 , mounting type: TS 35/7.5, TS 35/15 ,TS 32

### Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
UPDD	Height : 52.25 mm Width : 2.50 mm Length : 56.00 mm	
Fixed Bridge		
SLU4-2W	Height : 13.00 mm Pitch : 6.00 mm Length : 10.40 mm	
SLU4-10W	Height : 13.00 mm Pitch : 6.00 mm Length : 58.40 mm	
SLU4-3W	Height : 13.00 mm Pitch : 6.00 mm Length : 16.40 mm	
SLU4-4W	Height : 13.00 mm Pitch : 6.00 mm Length : 22.40 mm	
SLU4-5W	Height : 13.00 mm Pitch : 6.00 mm Length : 28.40 mm	

Marker For Terminal Blocks		
LABEL U6.2	Height : 4.00 mm Pitch : 6.20 mm Length : 10.60 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	