

## UBT2.5

Terminal Type - UBT2.5 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 28 A, Rated cross-section - 2.5 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 24 - 12 , mounting type: TS 35/7.5, TS 35/15 , TS 32

### Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
UPNS	Height : 63.00 mm Width : 2.00 mm Length : 85.00 mm	
<b>Fixed Bridge</b>		
SLU4-2W	Height : 13.00 mm Pitch : 6.00 mm Length : 10.40 mm	
SLU4-10W	Height : 13.00 mm Pitch : 6.00 mm Length : 58.40 mm	
SLU4-3W	Height : 13.00 mm Pitch : 6.00 mm Length : 16.40 mm	

<b>Fixed Bridge</b>		
SLU4-4W	Height : 13.00 mm Pitch : 6.00 mm Length : 22.40 mm	
SLU4-5W	Height : 13.00 mm Pitch : 6.00 mm Length : 28.40 mm	
<b>Marker For Terminal Blocks</b>		
LABEL U6	Pitch : 6.00 mm	
<b>Partition Plate</b>		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	