







UBT6

Terminal Type - UBT6 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 41 A, connection method: Screw connection, number of connections: 2, Rated cross section: 6.0 mm² , cross section: 0.5 mm² - 10 mm², AWG: 24 - 8, mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
UPX	Height : 72.00 mm Width : 4.00 mm Length : 85.00 mm	
Fixed Bridge		
SLU6-2W	Height : 17.00 mm Pitch : 8.00 mm Length : 13.70 mm	
SLU6-10W	Height : 17.00 mm Pitch : 8.00 mm Length : 78.50 mm	
SLU6-3W	Height : 17.00 mm Pitch : 8.00 mm Length : 21.80 mm	
SLU6-4W	Height : 17.00 mm Pitch : 8.00 mm Length : 29.90 mm	

Fixed Bridge		
SLU6-5W	Height : 17.00 mm Pitch : 8.00 mm Length : 38.00 mm	
Marker For Terminal Blocks		
LABEL U8	Pitch : 8.00 mm	
Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	