



## **CBTM4NVS11**

Terminal Type - CBTM4NVS11, Stud Type terminal block, nominal voltage: 1100 V, nominal current: 57 A, Rated cross-section - 10 mm<sup>2</sup>, connection method: Bolt connection - Nut Driver Operated, number of connections: 2, cross-section: 2.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type : TS32



### Approvals

CE

### General Information

Product Name	CBTM4NVS11
Connection Method	Bolt Connection
Rating	1100 V/57 A/10 mm <sup>2</sup> /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	15 mm	0.59 inch
Length	46 mm	1.81 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.34 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

### Rated Conductor Size


Conductor cross section flexible min	2.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	2.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1100 V
Nominal Current $I_n$	57 A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	57 kA
Rated surge voltage	8 kV
Degree of pollution	3

**Product Accessories**

**Cover Profile**











PCC3NV	Width : 300.00 mm Thickness : 1.50 mm Length : 48.50 mm	
PCCM30NV	Width : 30.00 mm Thickness : 1.00 mm Length : 45.50 mm	
PCCM45K	Width : 45.00 mm Thickness : 1.30 mm Length : 54.50 mm	



**DIN Rail Perforated**

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---

**End Clamp**

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

<b>End Clamp</b>		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
EPS4NV	Height : 28.50 mm Width : 2.50 mm Length : 46.00 mm	
<b>Insertion Bridge</b>		
KSL5-10W	Width : 142.50 mm Pitch : 15.00 mm Length : 26.50 mm	
KSL5-2W	Width : 37.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-3W	Width : 22.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-4W	Width : 52.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-5W	Width : 67.50 mm Pitch : 15.00 mm Length : 26.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN6.5	Width : 6.70 mm	
<b>Partition Plate</b>		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

