


CST2.5WS

Terminal Type - CST2.5WS, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 32 A , Rated cross-section – 4.0 mm², connection method: Screw connection with spring support, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS32, colour : KHAKHI



Approvals

CE

General Information

Product Name	CST2.5WS
Connection Method	Screw Connection with spring support
Rating	800 V/32 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	M3

Dimensions & Weight

Width	6.7 mm	0.26 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	1.7 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC


Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	32 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories

Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--

DIN Rail Perforated



CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---

End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	
Fixed Bridge		
CCLA2.5-10W	Height : 20.00 mm Pitch : 6.75 mm Length : 66.10 mm	
CCLA2.5-3W	Height : 20.00 mm Pitch : 6.75 mm Length : 18.70 mm	
CCLA2.5-4W	Height : 20.00 mm Pitch : 6.75 mm Length : 25.60 mm	
CCLA2.5-5W	Height : 20.00 mm Pitch : 6.75 mm Length : 32.35 mm	
CCLA2.5-6W	Height : 20.00 mm Pitch : 6.75 mm Length : 39.00 mm	
CCLA2.5-8W	Height : 20.00 mm Pitch : 6.75 mm Length : 52.60 mm	
CCLA2.5-2W	Height : 20.00 mm Pitch : 6.75 mm Length : 11.90 mm	

Insertion Bridge		
SLC2.5-2W	Width : 12.50 mm Pitch : 6.70 mm Length : 26.00 mm	
SLC2.5-10W	Width : 65.10 mm Pitch : 6.70 mm Length : 25.00 mm	
SLC2.5-4W	Width : 24.90 mm Pitch : 6.70 mm Length : 25.00 mm	
SLC2.5-5W	Width : 31.60 mm Pitch : 6.70 mm Length : 25.00 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL2.5	Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm	
Warning Label		
WL2.5	Height : 24.00 mm Thickness : 1.10 mm Length : 24.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	