


CST35

Terminal Type - CST35, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 125 A , Rated cross-section - 35 mm², connection method: Screw connection, number of connections: 2, cross-section: 10 mm² - 50 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CST35
Connection Method	Screw Connection
Rating	800 V/125 A/35 mm ² /4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	18 mm	0.71 inch
Length	58 mm	2.28 inch
Height	65 mm	2.56 inch
Weight of std. Packing Unit	3.87 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	50 mm ²

Ratings - IEC


Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	125 A
Nominal cross section	35 mm ²
Short-time current	4.20 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories

Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---




Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--


DIN Rail Perforated


CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---

End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPZ	Height : 52.00 mm Width : 2.50 mm Length : 58.00 mm	
Fixed Bridge		
CCLA35K-2W	Height : 27.00 mm Pitch : 17.00 mm Length : 25.50 mm	
CCLA35K-10W	Height : 27.00 mm Pitch : 17.00 mm Length : 165.00 mm	
CCLA35K-3W	Height : 27.00 mm Pitch : 17.00 mm Length : 42.50 mm	
CCLA35K-4W	Height : 27.00 mm Pitch : 17.00 mm Length : 60.00 mm	
CCLA35K-5W	Height : 27.00 mm Pitch : 17.00 mm Length : 77.50 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
BPZ	Height : 76.00 mm Width : 3.30 mm Length : 73.00 mm	

Warning Label		
WL35	Width : 35.00 mm Thickness : 1.50 mm Length : 74.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

