


CST6

Terminal Type - CST6, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 41 A, Rated cross-section - 6.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CST6
Connection Method	Screw Connection
Rating	800 V/41 A/6 mm ² /0.8 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	1.67 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC


Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories

Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---




Cover Profile Carrier











UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--



DIN Rail Perforated

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---





End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	
Fixed Bridge		
CCLA6-2W	Height : 20.00 mm Pitch : 8.00 mm Length : 13.50 mm	
CCLA6-10W	Height : 20.00 mm Pitch : 8.00 mm Length : 78.10 mm	
CCLA6-3W	Height : 20.00 mm Pitch : 8.00 mm Length : 21.60 mm	
CCLA6-4W	Height : 20.00 mm Pitch : 8.00 mm Length : 29.70 mm	
CCLA6-5W	Height : 20.00 mm Pitch : 8.00 mm Length : 37.70 mm	
CCLA6-6W	Height : 20.00 mm Pitch : 8.00 mm Length : 45.80 mm	
CCLA6-7W	Height : 20.00 mm Pitch : 8.00 mm Length : 53.90 mm	

Insertion Bridge		
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	

Datasheet

Switching Jumper		
RSL6	Thickness : 1.20 mm Pitch : 8.00 mm Length : 13.80 mm	
Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	