


CUT4

Terminal Type - CUT4, Feed-through terminal block, nominal voltage: 750 V, nominal current: 32 A, Rated cross-section - 4.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS32



Approvals

CE

General Information

| | |
|-----------------------------|--------------------------------------|
| Product Name | CUT4 |
| Connection Method | Screw Connection |
| Rating | 750 V/32 A/4 mm ² /0.5 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | M3 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 6.7 mm | 0.26 inch |
| Length | 40 mm | 1.57 inch |
| Height | 49 mm | 1.93 inch |
| Weight of std. Packing Unit | 1.21 Kg | |

Material Data

| | |
|---------------------|-------------------------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Khakhi |
| Colour Variants | Red , Yellow , Blue , Black , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 4 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 6 mm ² |

Ratings - IEC


| | |
|----------------------------------|-------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 750 V |
| Nominal Current I_n | 32 A |
| Nominal cross section | 4 mm ² |
| Short-time current | 0.48 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

Product Accessories

Cover Profile

| | | |
|------|--|---|
| PCK3 | Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm |  |
|------|--|---|





Cover Profile Carrier

| | | |
|------|---|--|
| UHDD | Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm |  |
|------|---|--|

DIN Rail Perforated



| | | |
|-----|--|---|
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
|-----|--|---|

End Clamp

| | | |
|-------|---|---|
| SCS | Height : 26.90 mm Length : 21.00 mm |  |
| SCSN | Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm |  |
| SCUP | Height : 34.00 mm Length : 44.75 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |

| End Clamp | | |
|---------------------|--|---|
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| EPX | Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm |  |
| Fixed Bridge | | |
| CCLA2.5-10W | Height : 20.00 mm Pitch : 6.75 mm Length : 66.10 mm |  |
| CCLA2.5-3W | Height : 20.00 mm Pitch : 6.75 mm Length : 18.70 mm |  |
| CCLA2.5-4W | Height : 20.00 mm Pitch : 6.75 mm Length : 25.60 mm |  |
| CCLA2.5-5W | Height : 20.00 mm Pitch : 6.75 mm Length : 32.35 mm |  |
| CCLA2.5-6W | Height : 20.00 mm Pitch : 6.75 mm Length : 39.00 mm |  |
| CCLA2.5-8W | Height : 20.00 mm Pitch : 6.75 mm Length : 52.60 mm |  |
| CCLA2.5-2W | Height : 20.00 mm Pitch : 6.75 mm Length : 11.90 mm |  |

| Insertion Bridge | | |
|----------------------------|---|---|
| SLC2.5-2W | Width : 12.50 mm Pitch : 6.70 mm Length : 26.00 mm |  |
| SLC2.5-10W | Width : 65.10 mm Pitch : 6.70 mm Length : 25.00 mm |  |
| SLC2.5-4W | Width : 24.90 mm Pitch : 6.70 mm Length : 25.00 mm |  |
| SLC2.5-5W | Width : 31.60 mm Pitch : 6.70 mm Length : 25.00 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN6.5 | Width : 6.70 mm |  |
| Partition Plate | | |
| KBXF | Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm |  |
| Switching Jumper | | |
| LSR2.5-6 | Height : 23.00 mm Width : 5.00 mm |  |
| RSL2.5 | Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm |  |
| Warning Label | | |
| WL2.5 | Height : 24.00 mm Thickness : 1.10 mm Length : 24.00 mm |  |
| Marker carriers | | |
| GMC | Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm |  |

| Marker carriers | | |
|------------------------|--|---|
| SCUDDMLH | Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm |  |

