



DBK150/16-1X2

Terminal Type - DBK150/16-1X2 , Distribution Block, nominal voltage: 800 V, nominal current:IC-269 A , OG-76 A , Rated cross-section- IC-150 mm², OG-16 mm² ,connection method: 1 Nut connection for IC & Screw connection for OG, number of connections: 5 , cross-section: IC- 50 - 150 mm² , OG -6-16 mm² , mounting type: TS35/7.5, TS35/15 , TS32



Approvals

CE

General Information

Product Name	DBK150/16-1X2
Connection Method	1 nut connection for IC & Screw clamp connection for OG
Rating	800 V/IC-269 A, OG-76 A/IC-150 mm ² , OG-16 mm ² /IC-14 Nm , OG-1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	8
Country Of Origin	India
Screw thread	IC-M12 , OG-M4

Dimensions & Weight

Width	62 mm	2.44 inch
Length	82 mm	3.23 inch
Height	69.5 mm	2.74 inch
Weight of std. Packing Unit	1.58 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi , Gray ,

Rated Conductor Size

Conductor cross section flexible min	IC-50 mm ² , OG-6 mm ²
Conductor cross section flexible max	IC-150 mm ² , OG-16 mm ²
Conductor cross section solid min	IC-50 mm ² , OG-6 mm ²
Conductor cross section solid max	IC-150 mm ² , OG-16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	IC-269 A, OG-76 A
Nominal cross section	IC-150 mm ² , OG-16 mm ²
Short-time current	18 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories



Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---



Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Partition Plate		
KBT	Height : 53.00 mm Width : 1.50 mm Length : 59.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	

