



DPSC5.08WF-24W

Terminal Type - DPSC5.08WF - 24W , Plug & socket type terminal block with additional holding strip , nominal voltage: 250 V, nominal current: 16 A, Rated cross-section - 2.5 mm², connection method: Spring cage connection, number of connections: 48, cross-section: 0.2 mm² - 2.5 mm², mounting type: TS35/7.5, TS35/15



Approvals

CE

General Information

| | |
|-----------------------------|-------------------------------------|
| Product Name | DPSC5.08WF-24W |
| Connection Method | Spring Cage Connection |
| Rating | 250 V/16 A/2.5 mm ² / Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 1 |
| Country Of Origin | India |
| Screw thread | NAV |

Dimensions & Weight

| | | |
|-----------------------------|-----------|-----------|
| Width | 127.65 mm | 5.03 inch |
| Length | 58.51 mm | 2.3 inch |
| Height | 26.15 mm | 1.03 inch |
| Weight of std. Packing Unit | 0.13 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , |

Rated Conductor Size



| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.2 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.2 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Ratings - IEC


| | |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 250 V |
| Nominal Current I_n | 16 A |
| Nominal cross section | 2.5 mm ² |
| Short-time current | 0.18 kA |
| Rated surge voltage | 4 kV |
| Degree of pollution | 3 |

Product Accessories

DIN Rail Perforated

| | | |
|-------|--|--|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

DIN Rail, Unperforated

| | | |
|------|--|---|
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

End Cap

| | | |
|-----------|---|---|
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
|-----------|---|---|

Marker For Terminal Blocks

| | | |
|--------------|-----------------|---|
| LABEL KN5.08 | Pitch : 5.08 mm |  |
|--------------|-----------------|---|

Tool

| | | |
|---------|--|---|
| DPSCCOT | Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm |  |
|---------|--|---|