



## **DSDT2.5WOSL**

Terminal Type - DSDT2.5WOSL, Disconnecting terminal block without provision of Shorting Link, nominal voltage: 1000 V, nominal current: 17.5 A, Rated cross-section – 2.5 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals

CE

### General Information

Product Name	DSDT2.5WOSL
Connection Method	Spring Cage Connection
Rating	1000 V/17.5 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	60 mm	2.36 inch
Height	37.5 mm	1.48 inch
Weight of std. Packing Unit	1.2 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Orange , Blue , Black , Green ,

### Rated Conductor Size



Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

## Ratings - IEC



Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	17.5 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	8 kV
Degree of pollution	3

## Product Accessories

### DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

### DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

### End Clamp

SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	

<b>End Clamp</b>		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
DPDT2.5WOSL	Height : 23.00 mm Thickness : 2.00 mm Length : 60.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5	Width : 5.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	