



## KUF10

Terminal Type - KUF10, Fuse terminal block, nominal voltage: 1000 V, nominal current: 12 A, Rated cross-section - 10 mm<sup>2</sup>, suitable size of cartridge fuse: 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 18 - 6, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals



### General Information

Product Name	KUF10
Connection Method	Screw Connection
Rating	1000 V/12 A/10 mm <sup>2</sup> /1.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	12 mm	0.47 inch
Length	66 mm	2.6 inch
Height	63.5 mm	2.5 inch
Weight of std. Packing Unit	2.07 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 6947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	12 A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage $U_n$	750 V
ATEX Nominal Current $I_n$	10 A
ATEX Cross Sec. Flexible Max.	10 mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	600 V
B - CSA Nominal Current $I_N$	12 A
B - CSA Wire Min	18 AWG
B - CSA Wire Max	6 AWG

### Ratings - UL







UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	12 A
B - UL Wire Min	18 AWG
B - UL Wire Max	6 AWG

### Product Accessories

#### DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

<b>End Cover</b>		
EPF	Height : 46.20 mm Width : 3.00 mm Length : 66.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN12	Width : 12.00 mm	
<b>Partition Plate</b>		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	