


KUT4-2X2

Terminal Type - KUT4-2X2 , Multi Conductor Feed-through terminal block, nominal voltage: 800 V, nominal current: 24 A, connection method: Screw connection, number of connections: 4, Rated cross section: 4.0 mm², cross section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals

CE

General Information

Product Name	KUT4-2X2
Connection Method	Screw Connection
Rating	800 V/24 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	67 mm	2.64 inch
Height	53 mm	2.09 inch
Weight of std. Packing Unit	1.83 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	24 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories



Cover Profile

PCPDBF-4	Height : 13.10 mm Thickness : 1.00 mm Length : 95.00 mm	
----------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	











DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPMD4	Height : 42.40 mm Width : 1.50 mm Length : 67.00 mm	
Fixed Bridge		
CCLA4N-10W	Height : 17.00 mm Pitch : 6.00 mm Length : 58.60 mm	
CCLA4N-3W	Height : 17.00 mm Pitch : 6.00 mm Length : 16.60 mm	
CCLA4N-4W	Height : 17.00 mm Pitch : 6.00 mm Length : 22.80 mm	

Fixed Bridge		
CCLA4N-5W	Height : 17.00 mm Pitch : 6.00 mm Length : 28.60 mm	
CCLA4N-2W	Height : 17.00 mm Pitch : 6.00 mm Length : 10.60 mm	
Insertion Bridge		
SLC4N-10W	Width : 58.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-3W	Width : 16.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-4W	Width : 22.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-5W	Width : 28.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-6W	Width : 34.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-2W	Width : 10.91 mm Pitch : 6.00 mm Length : 23.00 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
DBF-4	Height : 45.40 mm Thickness : 3.00 mm Length : 90.00 mm	

Switching Jumper		
LSR6N	Height : 22.20 mm Width : 5.00 mm	
RSLDD	Thickness : 1.20 mm Pitch : 6.00 mm Length : 11.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	