



PQD6

Terminal Type - PQD6 , Knife Disconnect Terminal Blocks , nominal voltage: 1000 V, nominal current: 30 A, Rated Cross section - 6 mm², connection method: Push in type, number of connections: 2, cross-section: 0.2 mm² - 10 mm², AWG : 24-8 , mounting type: TS 35/7.5, TS 35/15.



Approvals

CE

General Information

Product Name	PQD6
Connection Method	Push In Connection
Rating	1000 V/30 A/6 mm ² /NAV Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	8 mm	0.31 inch
Length	104.2 mm	4.1 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	0 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	30 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	0 V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	C.22.2 NO.:158
B - CSA Nominal Voltage U_n	600 V
B - CSA Nominal Current I_n	30 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_n	600 V
B - UL Nominal Current I_n	30 A
B - UL Wire Min	24 AWG
B - UL Wire Max	8 AWG











Product Accessories


Cover Profile









PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
--------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
-------	--	---

DIN Rail Perforated		
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	

End Clamp		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSPD6	Height : 42.00 mm Thickness : 2.00 mm Length : 105.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
BPN70	Height : 67.50 mm Width : 3.00 mm Length : 125.00 mm	
Plug-in Bridge/Jumper		
SLPU8-2W	Height : 33.30 mm Width : 15.20 mm Pitch : 8.00 mm	
SLPU8-10W	Height : 33.30 mm Width : 79.20 mm Pitch : 8.00 mm	
SLPU8-3W	Height : 33.30 mm Width : 23.20 mm Pitch : 8.00 mm	
SLPU8-4W	Height : 33.30 mm Width : 31.20 mm Pitch : 8.00 mm	
SLPU8-5W	Height : 33.30 mm Width : 39.20 mm Pitch : 8.00 mm	
SLPU8-6W	Height : 33.30 mm Width : 47.20 mm Pitch : 8.00 mm	

Plug-in Bridge/Jumper		
SLPU8-3AW	Height : 33.30 mm Width : 2.50 mm Pitch : 16.00 mm Length : 23.20 mm	
SLPU8-7AW	Height : 33.30 mm Width : 2.50 mm Pitch : 16.00 mm Length : 55.20 mm	
Switching Jumper		
SJD6BIM (2W, 3W, 4W)	Height : 47.25 mm Width : 24.70 mm Length : 31.70 mm	
Test Adapter / Test Socket		
ADP6-Yellow	Height : 51.80 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	
Switching Lock		
SLPQD6	Height : 13.77 mm Width : 7.80 mm Length : 13.32 mm	
Operating lever		
HPQD6 (1W,2W,3W,4W)	Height : 14.85 mm Width : 13.00 mm Length : 31.70 mm	