



## SPT120

Terminal Type - SPT120, High current connectors with secured hinged cover, nominal voltage: 1500 V, nominal current: 269 A, Rated cross-section - 120 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 16 mm<sup>2</sup> - 120 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals

CE

### General Information

Product Name	SPT120
Connection Method	Bolt Connection
Rating	1000 V/269 A/120 mm <sup>2</sup> /10 Nm
HSN Number	85389000
Standard Packing Qty(in No)	4
Country Of Origin	India
Screw thread	M10

### Dimensions & Weight

Width	42 mm	1.65 inch
Length	225.7 mm	8.89 inch
Height	80.3 mm	3.16 inch
Weight of std. Packing Unit	1.4 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size



Conductor cross section flexible min	10 mm <sup>2</sup>
Conductor cross section flexible max	120 mm <sup>2</sup>
Conductor cross section solid min	10 mm <sup>2</sup>
Conductor cross section solid max	120 mm <sup>2</sup>

## Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	269 A
Nominal cross section	120 mm <sup>2</sup>
Short-time current	14.4 kA
Rated surge voltage	8 kV
Degree of pollution	3

## Product Accessories

### DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	


### DIN Rail, Unperforated


CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

### End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

### End Clamp

SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

<b>End Clamp</b>		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
<b>Fixed Bridge</b>		
CCLASPT150-2W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
CCLASPT150-3W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN12	Width : 12.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	