


SPT95

Terminal Type - SPT95, High current connectors with secured hinged cover, nominal voltage: 1000 V, Rated cross-section - 95 mm², nominal current: 232 A, connection method: Bolt connection, number of connections: 2, cross-section: 16 mm² - 95 mm², mounting type: TS 35/7.5, TS 35/15, colour : GREY



Approvals

CE

General Information

Product Name	SPT95
Connection Method	Bolt Connection
Rating	1000 V/232 A/95 mm ² /6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M8

Dimensions & Weight

Width	32 mm	1.26 inch
Length	180 mm	7.09 inch
Height	71 mm	2.8 inch
Weight of std. Packing Unit	2.1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size



Conductor cross section flexible min	16 mm ²
Conductor cross section flexible max	95 mm ²
Conductor cross section solid min	16 mm ²
Conductor cross section solid max	95 mm ²

Ratings - IEC



Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	232 A
Nominal cross section	95 mm ²
Short-time current	11.4 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated



CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Fixed Bridge		
CCLASPT70-2W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 32.00 mm Length : 50.00 mm	
CCLASPT70-3W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 32.00 mm Length : 82.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	