


## CATM5NV

Terminal Type - CATM5NV, Stud Type terminal block, nominal voltage: 1100 V, nominal current: 76 A, Rated cross-section - 16 mm<sup>2</sup>, connection method: Bolt Connection - Screwdriver operated, number of connections: 2, cross-section: 2.5 mm<sup>2</sup> - 16 mm<sup>2</sup>, mounting type : TS32



### Approvals

CE

### General Information

Product Name	CATM5NV
Connection Method	Bolt Connection
Rating	1100 V/76 A/16 mm <sup>2</sup> /2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M5

### Dimensions & Weight

Width	13 mm	0.51 inch
Length	46 mm	1.81 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.42 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

### Rated Conductor Size

Conductor cross section flexible min	2.5 mm <sup>2</sup>
Conductor cross section flexible max	16 mm <sup>2</sup>
Conductor cross section solid min	2.5 mm <sup>2</sup>
Conductor cross section solid max	16 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1100 V
Nominal Current $I_n$	76 A
Nominal cross section	16 mm <sup>2</sup>
Short-time current	1.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

