


## CBTM6S1

Terminal Type - CBTM6S1 , Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 125 A, Rated cross-section - 35 mm<sup>2</sup> connection method: Bolt Connection - Nut Driver Operated, number of connections: 2, cross section: 6 mm<sup>2</sup> - 35 mm<sup>2</sup> , mounting type: TS32



### Approvals

CE

### General Information

Product Name	CBTM6S1
Connection Method	Bolt Connection
Rating	1100 V/125 A/35 mm <sup>2</sup> /2.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	India
Screw thread	M6

### Dimensions & Weight

Width	26 mm	1.02 inch
Length	52 mm	2.05 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.82 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

### Rated Conductor Size

Conductor cross section flexible min	6 mm <sup>2</sup>
Conductor cross section flexible max	35 mm <sup>2</sup>
Conductor cross section solid min	6 mm <sup>2</sup>
Conductor cross section solid max	35 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1100 V
Nominal Current $I_n$	125 A
Nominal cross section	35 mm <sup>2</sup>
Short-time current	4.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

