


CST16

Terminal Type - CST16, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 76 A , Rated cross-section - 16 mm², connection method: Screw connection, number of connections: 2, cross-section: 6 mm² - 25 mm², mounting type: TS32



Approvals

CE

General Information

| | |
|-----------------------------|---------------------------------------|
| Product Name | CST16 |
| Connection Method | Screw Connection |
| Rating | 800 V/76 A/16 mm ² /1.2 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 50 |
| Country Of Origin | India |
| Screw thread | M4 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 12 mm | 0.47 inch |
| Length | 45 mm | 1.77 inch |
| Height | 55 mm | 2.17 inch |
| Weight of std. Packing Unit | 1.64 Kg | |

Material Data

| | |
|---------------------|---------------------------------------|
| Insulating Material | Melamine |
| Standard Colour | Khakhi |
| Colour Variants | Red , Yellow , Blue , Black , Green , |

Rated Conductor Size

| | |
|--------------------------------------|--------------------|
| Conductor cross section flexible min | 6 mm ² |
| Conductor cross section flexible max | 16 mm ² |
| Conductor cross section solid min | 6 mm ² |
| Conductor cross section solid max | 25 mm ² |

Ratings - IEC

| | |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 800 V |
| Nominal Current I_n | 76 A |
| Nominal cross section | 16 mm ² |
| Short-time current | 1.92 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

