


CST185

Terminal Type - CST185, High current feed through Terminal block, nominal voltage: 800 V, nominal current: 353 A, Rated cross-section - 185 mm², connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² - 240 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CST185
Connection Method	Bolt Connection
Rating	800 V/353 A/185 mm ² /14 Nm
HSN Number	85389000
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	M10

Dimensions & Weight

Width	38 mm	1.5 inch
Length	105 mm	4.13 inch
Height	113 mm	4.45 inch
Weight of std. Packing Unit	4.1 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	185 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	240 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	353 A
Nominal cross section	185 mm ²
Short-time current	22.20 kA
Rated surge voltage	8 kV
Degree of pollution	3

