


## CST2.5

Terminal Type - CST2.5, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 32 A, Rated cross-section - 4.0 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: TS32



### Approvals

CE

### General Information

Product Name	CST2.5
Connection Method	Screw Connection
Rating	800 V/32 A/4 mm <sup>2</sup> /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	6.7 mm	0.26 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	1.42 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	800 V
Nominal Current $I_n$	32 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

