


CST35

Terminal Type - CST35, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 125 A , Rated cross-section - 35 mm², connection method: Screw connection, number of connections: 2, cross-section: 10 mm² - 50 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CST35
Connection Method	Screw Connection
Rating	800 V/125 A/35 mm ² /4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	18 mm	0.71 inch
Length	58 mm	2.28 inch
Height	65 mm	2.56 inch
Weight of std. Packing Unit	3.87 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	50 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	125 A
Nominal cross section	35 mm ²
Short-time current	4.20 kA
Rated surge voltage	8 kV
Degree of pollution	3

