


CST70

Terminal Type - CST70, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 192 A , Rated cross-section - 75 mm², connection method: Screw connection, number of connections: 2, cross-section: 10 mm² - 95 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CST70
Connection Method	Screw Connection
Rating	800 V/192 A/70 mm ² /6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	27 mm	1.06 inch
Length	76.5 mm	3.01 inch
Height	78.7 mm	3.1 inch
Weight of std. Packing Unit	1.45 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	70 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	95 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	192 A
Nominal cross section	70 mm ²
Short-time current	8.4 kA
Rated surge voltage	8 kV
Degree of pollution	3

