



## **CUDD4S**

Terminal Type - CUDD4S, Multi-level terminal block, nominal voltage: 500 V, nominal current: 20 A, Rated cross-section - 2.5 mm<sup>2</sup>, connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS32



### Approvals

CE

### General Information

Product Name	CUDD4S
Connection Method	Screw Connection
Rating	500 V/20 A/2.5 mm <sup>2</sup> /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	50 mm	1.97 inch
Height	54 mm	2.13 inch
Weight of std. Packing Unit	0.7 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

## Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	500 V
Nominal Current $I_n$	20 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

