


CUT10

Terminal Type - CUT10 , Feed-through terminal block, nominal voltage: 750 V, nominal current: 57 A, Rated cross-section - 10.0 mm², connection method: Screw connection, number of connections: 2, cross section: 1.5 mm² - 16 mm², mounting type: TS32



Approvals

CE

General Information

| | |
|-----------------------------|---------------------------------------|
| Product Name | CUT10 |
| Connection Method | Screw Connection |
| Rating | 750 V/57 A/10 mm ² /1.2 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | M4 |

Dimensions & Weight

| | | |
|-----------------------------|--------|-----------|
| Width | 10 mm | 0.39 inch |
| Length | 40 mm | 1.57 inch |
| Height | 49 mm | 1.93 inch |
| Weight of std. Packing Unit | 2.1 Kg | |

Material Data

| | |
|---------------------|-------------------------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Khakhi |
| Colour Variants | Red , Yellow , Blue , Black , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 1.5 mm ² |
| Conductor cross section flexible max | 10 mm ² |
| Conductor cross section solid min | 1.5 mm ² |
| Conductor cross section solid max | 16 mm ² |

Ratings - IEC

| | |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 750 V |
| Nominal Current I_n | 57 A |
| Nominal cross section | 10 mm ² |
| Short-time current | 1.2 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

