



## **DPSC5.08WW-10W**

Terminal Type - DPSC5.08WW - 10W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, Rated cross-section - 2.5 mm<sup>2</sup>, connection method: Spring cage connection, number of connections: 20 , cross-section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: wire to wire or wire to board



### Approvals

CE

### General Information

Product Name	DPSC5.08WW-10W
Connection Method	Spring Cage Connection
Rating	250 V/16 A/2.5 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	66.69 mm	2.63 inch
Length	45.25 mm	1.78 inch
Height	14.45 mm	0.57 inch
Weight of std. Packing Unit	1.1 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Gray ,

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	250 V
Nominal Current $I_n$	16 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	4 kV
Degree of pollution	3

