



DPSC5.08WW-20W

Terminal Type - DPSC5.08WW - 20W , Plug & socket type terminal block with additional holding strip , nominal voltage: 250 V, nominal current: 16 A, Rated cross-section – 2.5 mm² , connection method: Spring cage connection , number of connections: 40, cross-section: 0.2 mm² - 2.5 mm², mounting type: wire to wire or wire to board



Approvals

CE

General Information

Product Name	DPSC5.08WW-20W
Connection Method	Spring Cage Connection
Rating	250 V/16 A/2.5 mm ² / Nm
HSN Number	85389000
Standard Packing Qty(in No)	1
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	117.49 mm	4.63 inch
Length	45.25 mm	1.78 inch
Height	14.45 mm	0.57 inch
Weight of std. Packing Unit	0.13 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	250 V
Nominal Current I_n	16 A
Nominal cross section	2.5 mm ²
Short-time current	0.18 kA
Rated surge voltage	4 kV
Degree of pollution	3

