



DSCDT6-4W

Terminal Type - DSCDT6-4W , Test Disconnect terminal block with internally shorted with shorting link , nominal voltage: 400 V, nominal current: 41 A, connection method: Spring Cage connection, number of connections: 8, cross section: 0.5 mm² - 6 mm² , AWG: 20-10, width: 8x4 mm , height: 41.5 mm , length : 87.5 mm , mounting type: TS 35/7.5, TS 35/15



Approvals

CE

General Information

Product Name	DSCDT6-4W
Connection Method	Spring Cage Connection
Rating	400 V/41 A/6 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	15
Country Of Origin	INDIA
Screw thread	NA

Dimensions & Weight

Width	32 mm	1.26 inch
Length	87.5 mm	3.44 inch
Height	41.5 mm	1.63 inch
Weight of std. Packing Unit	2.55 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	400 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	4 kV
Degree of pollution	3

