



## DSDDM2.5

Terminal Type - DSDDM2.5, Multi-level terminal block, nominal voltage: 500 V, nominal current: 20 A, Rated cross-section - 2.5 mm<sup>2</sup>, connection method: Spring cage connection, number of connections: 4, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, colour: GREY



### Approvals

CE

### General Information

|                             |  |
|-----------------------------|--|
| Product Name                | DSDDM2.5                               |
| Connection Method           | Spring Cage Connection                 |
| Rating                      | 500 V/20 A/2.5 mm <sup>2</sup> /NAP Nm |
| HSN Number                  | 85389000                               |
| Standard Packing Qty(in No) | 100                                    |
| Country Of Origin           | India                                  |
| Screw thread                | NAP                                    |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 5 mm    | 0.2 inch  |
| Length                      | 64 mm   | 2.52 inch |
| Height                      | 43.5 mm | 1.71 inch |
| Weight of std. Packing Unit | 1.02 Kg |           |

### Material Data

|                     |  |
|---------------------|--|
| Insulating Material | Polyamide 6,6                                  |
| Standard Colour     | Gray   |
| Colour Variants     | Red , Yellow , Blue , Black , Green , Khakhi , |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup> |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 2.5 mm <sup>2</sup> |

**Ratings - IEC**

|                                  |                     |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1       |
| Nominal Voltage $U_n$            | 500 V               |
| Nominal Current $I_n$            | 20 A                |
| Nominal cross section            | 2.5 mm <sup>2</sup> |
| Short-time current               | 0.3 kA              |
| Rated surge voltage              | 8 kV                |
| Degree of pollution              | 3                   |

