



## DSDT2.5WOSL

Terminal Type - DSDT2.5WOSL, Disconnecting terminal block without provision of Shorting Link, nominal voltage: 1000 V, nominal current: 17.5 A, Rated cross-section – 2.5 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals

CE

### General Information

Product Name	DSDT2.5WOSL
Connection Method	Spring Cage Connection
Rating	1000 V/17.5 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	60 mm	2.36 inch
Height	37.5 mm	1.48 inch
Weight of std. Packing Unit	1.2 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Orange , Blue , Black , Green ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	17.5 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	8 kV
Degree of pollution	3

