



## DST2.5-2C2P

Terminal Type - DST2.5-2C2P, Pluggable terminal block, nominal voltage: 500 V, nominal current: 16 A, Rated cross-section - 2.5 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 4, cross-section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, colour : GREY



### Approvals

CE

### General Information

Product Name	DST2.5-2C2P
Connection Method	Spring Cage Connection
Rating	500 V/16 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	5.08 mm	0.2 inch
Length	83 mm	3.27 inch
Height	33 mm	1.3 inch
Weight of std. Packing Unit	1.1 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	500 V
Nominal Current $I_n$	16 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	4 kV
Degree of pollution	3

