


DST6-1X2

Terminal Type - DST6-1X2 , Multi-Conductor terminal block, nominal voltage: 800 V, nominal current: 41 A, Rated cross-section - 6 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15, colour: GREY



Approvals

CE

General Information

Product Name	DST6-1X2
Connection Method	Spring Cage Connection
Rating	800 V/41 A/6 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	8 mm	0.31 inch
Length	93 mm	3.66 inch
Height	39.5 mm	1.56 inch
Weight of std. Packing Unit	2.31 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

